

N F 4H Panel Mount Solder for Semi-rigid .141/RG402 Cable

P/N: AT3N2S4-6A

Product Feature:

- Connector Type : N Type
- Polarity : Standard
- Gender : Female/jack
- Geometry : Straight (4Hole Flange Type)
- Termination Style : Solder
- Cable : Semi Rigid .141 / RG402
- Application : General Purpose/Military

The **N-Type Female 4-Hole Panel Mount Connector** is a rugged, high-frequency RF interface designed for **.141" semi-rigid and RG402 cables**. This connector features a square flange with four mounting holes for secure attachment to enclosures. Its direct-solder attachment provides excellent electrical continuity and mechanical strength. This makes it a preferred choice for **high-speed signal processing, laboratory test sets, and military aerospace assemblies** requiring reliable broadband performance.



Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 6	GHz
VSWR	≤ 1.15	@DC-3 GHz
	≤ 1.2	@3-5 GHz
Insertion Loss	≤ 0.05	@DC-5 GHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 2.5	kVrms
Inner Conductor Resistance	≤ 1.0	m Ω
Outer Conductor Resistance	≤ 0.25	m Ω
Power Handling	1.0	kW @1GHz
RF Leakage	≤ -90	dB @1GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Phosphorous bronze	Gold
Outer Conductor/Body	Brass	Tri-Alloy
Dielectric	PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (matings)	≥ 500 min.	-
Coupling nut torque	25/30	Nm
Cable Type Compatibility	Semi-rigid .141/RG402 Cable	-
Operating Temperature	-40 ~ 85	°C
Ingress Protection (IP Rating)	IP67	-
Compliance	ROHS	-