

N F Solder for 1/2" Super Flexible Cable

P/N: AT3N2S-6L

Product Feature:

- Connector Type : N Type
- Polarity : Standard
- Gender : Female/Jack
- Geometry : Straight
- Termination Style : Solder
- Cable : 1/2" Super Flexible
- Application: General Purpose/Telecom etc.

The **N Female Solder Connector** for **1/2" Super Flexible** cable is a high-performance RF interface designed for superior signal stability and low Passive Intermodulation (PIM). By utilizing a **solder-type center contact**, it provides a permanent, low-resistance electrical path essential for maintaining signal integrity in high-density networks. These connectors are primarily used in **cabinet penetrations, antenna jumpers, and test equipment interfaces** within **5G and DAS infrastructure**. Its rugged, weatherproof clamp design ensures a secure mechanical bond to the cable's corrugations, offering exceptional durability and moisture protection for critical indoor outdoor telecommunication.



Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 6	GHz
VSWR	≤ 1.15	@DC-3 GHz
	≤ 1.20	@3-5 GHz
Insertion Loss	≤ 0.05	@DC-5 GHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 2.5	kVrms
Inner Conductor Resistance	≤ 1.0	m Ω
Outer Conductor Resistance	≤ 0.25	m Ω
PIM	≤ -155	dBc@(2 \times 43dBm)
RF Leakage	≤ -85	dB @3GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Phosphor bronze	Silver
Outer Conductor/Body	Brass	Tri-Alloy
Shield Clamp	Brass	Nickel
Dielectric	PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Coupling nut torque	25/30	Nm
Cable Type Compatibility	1/2" Super Flexible Cable	-
Operating Temperature	-40 ~ 85	°C
Ingress Protection (IP Rating)	IP67	-
Compliance	ROHS	-