

N M CRIMP for LMR400/RG8/RG11/RG213/RG393 Cable

P/N: AT3N1D-6E

Product Feature:

- Connector Type : N Type
- Polarity : Standard
- Gender : Male/Plug
- Geometry : Straight
- Termination Style : Crimp
- Cable : LMR400/RG8/RG11/RG213/RG393
- Application : General Purpose/Military



The **N-Type Male Crimp Connector** is a heavy-duty, high-performance RF interface specifically engineered for large-diameter cables such as **LMR400, RG8, RG11, RG213, and RG393**. Featuring a robust threaded coupling and a high-strength crimp ferrule, it provides a secure, weatherproof connection with consistent **50-ohm impedance** up to 11 GHz. Its superior shielding and low VSWR make it the industry standard for **wireless infrastructure, telecommunication base stations, and high-power radio transmitters** requiring minimal signal loss.

Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 8	GHz
VSWR	≤ 1.15	@DC-3 GHz
	≤ 1.2	@3-5 GHz
Insertion Loss	≤ 0.05	@DC-5 GHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 2.5	kVrms
Inner Conductor Resistance	≤ 1.0	m Ω
Outer Conductor Resistance	≤ 0.25	m Ω
Power Handling	1.0	kW @1GHz
RF Leakage	≤ -90	dB @1GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Phosphorous bronze	Gold
Outer Conductor/Body	Brass	Tri-Alloy
Coupling Nut	Brass	Tri-Alloy
Ferrule	Brass	Tri-Alloy
Dielectric	PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (matings)	≥ 500 min.	-
Coupling nut torque	25/30	Nm
Cable Type Compatibility	LMR400/RG8/RG11/RG213/RG393 Cable	-
Operating Temperature	-40 ~ 85	°C
Ingress Protection (IP Rating)	IP67	-
Compliance	ROHS	-