

N M CRIMP for RG58/RG142/LMR195/LMR200 Cable P/N: AT3N1D-6D

Product Feature:

- Connector Type : N Type
- Polarity : Standard
- Gender : Male/Plug
- Geometry : Straight
- Termination Style : Crimp
- Cable : RG58/RG142/LMR195/LMR200
- Application : General Purpose/Telecom etc



The **N-Type Male Crimp Connector** is a heavy-duty RF interface designed for popular mid-sized coaxial cables such as **RG58, RG142, LMR195, and LMR200**.

This connector features a threaded coupling mechanism that provides a secure, weatherproof connection suitable for high-vibration environments.

The crimp-style termination ensures a **permanent, high-strength mechanical bond** and consistent 50-ohm impedance across frequencies up to 11 GHz. It is a standard choice for **WLAN installations, antenna feeders, and mobile communication systems**.

Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 8	GHz
VSWR	≤ 1.15	@DC-3 GHz
	≤ 1.2	@3-5 GHz
Insertion Loss	≤ 0.05	@DC-5 GHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 2.5	kVrms
Inner Conductor Resistance	≤ 1.0	m Ω
Outer Conductor Resistance	≤ 0.25	m Ω
Power Handling	1.0	kW @1GHz
RF Leakage	≤ -90	dB @1GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Phosphorous bronze	Gold
Outer Conductor/Body	Brass	Tri-Alloy
Coupling Nut	Brass	Tri-Alloy
Ferrule	Brass	Tri-Alloy
Dielectric	PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Coupling nut torque	25/30	Nm
Cable Type Compatibility	RG58/RG142/LMR195/LMR200 Cable	-
Operating Temperature	-40 ~ 85	°C
Ingress Protection (IP Rating)	IP67	-
Compliance	ROHS	-