

## N M CRIMP for RG6 Cable

P/N: AT3N1D-6U

### Product Feature:

- Connector Type : N Type
- Polarity : Standard
- Gender : Male/Plug
- Geometry : Straight
- Termination Style : Crimp
- Cable : RG6
- Application: General Purpose/Telecom etc.

The **N Male Crimp Connector for RG6 Cable** is a cost-effective, high-reliability RF component designed for efficient 50-ohm signal distribution. Utilizing a precision **crimp termination**, it ensures a fast and secure mechanical bond, making it ideal for high-volume field installations. This connector is widely used in **satellite television systems, CATV networks, and broadband internet distribution** where signal clarity is essential. Its rugged, nickel-plated construction and Silver/ gold-plated center pin provide excellent corrosion resistance and low insertion loss, ensuring a durable and stable interface for residential and **commercial telecommunications applications**.



### Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	$\Omega$
Frequency Range	DC ~ 6	GHz
VSWR	$\leq 1.15$	@DC-3 GHz
	$\leq 1.20$	@3-5 GHz
Insertion Loss	$\leq 0.05$	@DC-5 GHz
Insulation Resistance	$\geq 5000$	M $\Omega$
Dielectric Withstanding Voltage	$\geq 2.5$	kVrms
Inner Conductor Resistance	$\leq 1.0$	m $\Omega$
Outer Conductor Resistance	$\leq 0.25$	m $\Omega$
PIM	$\leq -155$	dBc@(2 $\times$ 43dBm)
RF Leakage	$\leq -85$	dB @3GHz



## Technical Data Sheet

<b>Material &amp; Plating</b>		
<b>Component</b>	<b>Material</b>	<b>Plating</b>
Center Conductor	Phosphor bronze	Silver/Gold
Outer Conductor/Body	Brass	Tri-Alloy
Coupling Nut	Brass	Nickel
Ferrule	Brass	Nickel
Dielectric	PTFE	-
Gasket	Silicone rubber	-

<b>Mechanical &amp; Environmental Specifications</b>		
<b>Parameter</b>	<b>Value</b>	<b>Unit</b>
Durability (Matings)	≥ 500 min.	-
Coupling nut torque	25/30	Nm
Cable Type Compatibility	RG6 Cable	-
Operating Temperature	-40 ~ 85	°C
Ingress Protection (IP Rating)	IP67	-
Compliance	ROHS	-