

## SMA F BH CRIMP for RG58/RG142/LMR195/LMR200 Cable

P/N: AT3S2DB-6D

### Product Feature:

- Connector Type : SMA
- Polarity : Standard
- Gender : Female/Jack
- Geometry : Straight Bulkhead
- Termination Style : Crimp
- Cable : RG58/RG142/LMR195/LMR200
- Application : General Purpose/Telecom etc

The **SMA Female Crimp Connector for RG58, RG142, LMR195, and LMR200 cables** provides a high-reliability, low-loss termination for mid-sized coaxial lines up to 6 GHz. Its robust rear **ferrule is precision-crimped** over the cable shield and jacket, delivering **excellent mechanical** pull-out resistance and **continuous electrical grounding**. The heavy-duty design handles both flexible and double-shielded, high-temperature cables with ease. It is extensively **deployed in cellular base stations, vehicular wireless telemetry systems, industrial IoT gateways, commercial WLAN installations, and RF laboratory test leads.**



### Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	$\Omega$
Frequency Range	DC ~ 6	GHz
VSWR	$\leq 1.15$	@DC-3 GHz
	$\leq 1.25$	@3-5 GHz
Insertion Loss	$\leq 0.2$	@DC-4 GHz
Insulation Resistance	$\geq 5000$	M $\Omega$
Dielectric Withstanding Voltage	$\geq 1.0$	kVrms (at sea level)
Inner Conductor Resistance	$\leq 3.0$	m $\Omega$
Outer Conductor Resistance	$\leq 2.0$	m $\Omega$
Power Handling	350	W @1GHz
RF Leakage	$\leq -60$	dB @1GHz



## Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Brass	Gold
Outer Conductor/Body	Brass	Gold
Ferrule	Copper Alloy	Nickel
Dielectric	Teflon/PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Fastening Type	1/4-36	-
Contact Captivation	≥ 27	N
Cable Type Compatibility	RG58/RG142/LMR195/LMR200 Cable	-
Operating Temperature	-50 ~ 125	°C
Compliance	ROHS	-