

SMA F RA for PCB solder with stand off

P/N: AT3S4PF-6

Product Feature:

- Connector Type : SMA
- Polarity : Standard
- Gender : Female/Jack
- Geometry : Right Angle (90°)
- Termination Style : Solder
- Mounting : To PCB (With Stand off)
- Application : General Purpose/Telecom etc



The **SMA Female Right-Angle Through-Hole PCB Solder Connector with built-in standoffs** provides a mechanically rugged, production-friendly interface for high-frequency layouts. Its **90-degree configuration** routes cables parallel to the board, while the **integrated standoff legs lift the body to prevent solder bridging and facilitate thorough post-reflow flux cleaning**. The through-hole pins anchor deeply into the substrate, effortlessly absorbing high installation torque. This design is widely specified in **industrial IoT gateways, automotive telemetry modules, base station subassemblies, and high-density RF matrices** where physical durability and clean **50 Ω impedance** are essential.

Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 6	GHz
VSWR	≤ 1.20	@DC-3 GHz
	≤ 1.30	@3-5 GHz
Insertion Loss	≤ 0.2	@DC-4 GHz
Insulation Resistance	≥ 5000	MΩ
Dielectric Withstanding Voltage	≥ 1.0	kVrms (at sea level)
Inner Conductor Resistance	≤ 3.0	mΩ
Outer Conductor Resistance	≤ 2.0	mΩ
Power Handling	350	W @1GHz
RF Leakage	≤ -60	dB @1GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Brass	Gold
Outer Conductor/Body	Brass	Gold
Dielectric	Teflon/PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Fastening Type	1/4-36	-
Contact Captivation	≥ 27	N
Soldered On	PCB (with stand off)	-
Operating Temperature	-50 ~ 125	°C
Compliance	ROHS	-