

SMA F RP CRIMP for RG58/RG142/LMR195/LMR200 Cable

P/N: AT3S2D-6D2

Product Feature:

- Connector Type : SMA
- Polarity : Reverse Polarity
- Gender : Female/Jack
- Geometry : Straight
- Termination Style : Crimp
- Cable : RG58/RG142/LMR195/LMR200
- Application : General Purpose/Telecom etc

The **Reverse Polarity (RP) SMA Female Crimp Connector for RG58, RG142, LMR195, and LMR200 cables** provides a secure, regulatory-compliant RF termination for flexible sub-miniature coax. Featuring a **male center pin inside a female threaded body**, this **RP-SMA configuration** meets standard wireless regulations by preventing unauthorized antenna swaps. The rear hex crimp sleeve ensures **excellent cable retention and electrical grounding** on thin Cables. It is **widely implemented in consumer and industrial Wi-Fi routers, wireless access points, Bluetooth gateways, and generic short-range ISM band radio communication modules.**



Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 6	GHz
VSWR	≤ 1.15	@DC-3 GHz
	≤ 1.25	@3-5 GHz
Insertion Loss	≤ 0.2	@DC-4 GHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 1.0	kVrms (at sea level)
Inner Conductor Resistance	≤ 3.0	m Ω
Outer Conductor Resistance	≤ 2.0	m Ω
Power Handling	350	W @1GHz
RF Leakage	≤ -60	dB @1GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Brass	Gold
Outer Conductor/Body	Brass	Gold
Ferrule	Copper Alloy	Nickel
Dielectric	Teflon/PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Fastening Type	1/4-36	-
Contact Captivation	≥ 27	N
Cable Type Compatibility	RG58/RG142/LMR195/LMR200 Cable	-
Operating Temperature	-50 ~ 125	°C
Compliance	ROHS	-