

SMA M CRIMP for LMR240 Cable

P/N: AT3S1D-6F

Product Feature:

- Connector Type : SMA
- Polarity : Standard
- Gender : Male/Plug
- Geometry : Straight
- Termination Style : Crimp
- Cable : LMR240
- Application : General Purpose/Telecom etc

The **SMA Male Crimp Connector for LMR240 coaxial cable** is a high-performance RF connector designed to interface with low-loss, mid-sized cabling. Engineered for reliable high-frequency operations up to 6 GHz, its robust **crimp design** ensures a secure, vibration-resistant connection with **excellent mechanical strength** and **minimal signal attenuation**. Because the LMR240 cable offers lower loss over longer distances than thinner cables, this connector is widely used in **higher-power applications, including cellular base stations, Wi-Fi signal boosters, distributed antenna systems (DAS), drone control links, and precision RF testing equipment.**



Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 6	GHz
VSWR	≤ 1.15	@DC-3 GHz
	≤ 1.25	@3-5 GHz
Insertion Loss	≤ 0.2	@DC-4 GHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 1.0	kVrms (at sea level)
Inner Conductor Resistance	≤ 3.0	m Ω
Outer Conductor Resistance	≤ 2.0	m Ω
Power Handling	350	W @1GHz
RF Leakage	≤ -60	dB @1GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Brass	Gold
Outer Conductor/Body	Brass	Gold
Coupling Nut	Brass	Gold
Ferrule	Copper Alloy	Nickel
Dielectric	Teflon/PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Fastening Type	1/4-36	-
Contact Captivation	≥ 27	N
Coupling Nut Retention Force	≥ 270	N
Cable Type Compatibility	LMR240 Cable	-
Operating Temperature	-50 ~ 125	°C
Compliance	ROHS	-