

TNC F CRIMP for LMR400/RG8/RG213/RG393 Cable

P/N: AT3T2D-6E

Product Feature:

- Connector Type : TNC
- Polarity : Standard
- Gender : Female/Jack
- Geometry : Straight
- Termination Style : Crimp
- Cable : LMR400/RG8/RG213/RG393
- Application : General Purpose/Telecom etc

The **TNC Female Crimp Connector** for **LMR400, RG8, RG213, and RG393 Cables** is a high-performance RF interface designed for **permanent, low-loss terminations** on large-diameter coaxial cables. Featuring a robust threaded coupling, it provides **superior mechanical stability and vibration resistance** for high-power applications. The precision crimp sleeve ensures a high-strength, uniform bond that optimizes **shielding effectiveness** and **signal integrity**. It is extensively used in **cellular base stations, high-power RF amplifiers, maritime communication systems, and heavy-duty wireless infrastructure** where a **durable, permanent, and low-attenuation connection** is required.



Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 6	GHz
VSWR	≤ 1.15	@DC-3 GHz
	≤ 1.25	@3-5 GHz
Insertion Loss	≤ 0.2	@DC-4 GHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 1.5	kVrms (at sea level)
Inner Conductor Resistance	≤ 1.5	m Ω
Outer Conductor Resistance	≤ 0.2	m Ω
Power Handling	316	W @1GHz
RF Leakage	≤ -55	dB @1GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Brass	Gold
Outer Conductor/Body	Brass	Nickel
Ferrule	Brass	Nickel
Dielectric	Teflon/PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Fastening Type	7/16-28	-
Contact Captivation	≥ 27	N
Cable Retention Force	≥ 150	N
Cable Type Compatibility	LMR400/RG8/RG213/RG393 Cable	-
Operating Temperature	-40 ~ 85	°C
Compliance	ROHS	-

Ground floor, Plot No -20, (KH No-160/1,street No-3/2, samta Vihar, Mukandpur Extn., North West Delhi, Delhi-110042
 Contact: +91 9643592149 Email: info@aetherx.in , Website: www.aetherx.in