

TNC M CLAMP for 1/2" Super Flexible Cable

P/N: AT3T1C-6L

Product Feature:

- Connector Type : TNC
- Polarity : Standard
- Gender : Male/Plug
- Geometry : Straight
- Termination Style : Clamp
- Cable : 1/2" Super Flexible
- Application : General Purpose/Telecom etc

The **TNC Male Clamp Connector for 1/2" Super Flexible Cable** is a specialized RF solution designed to maximize performance in high-density installations. Its clamp-style assembly provides a secure, weather-resistant termination for super-flexible feeder lines **without needing complex crimping tools**. The threaded coupling mechanism ensures **superior stability and electrical contact**, even under constant vibration. This connector is widely used in **in-building DAS, small cell deployments, cellular base stations, and high-frequency jumper assemblies** where tight-radius bending and **low intermodulation (PIM)** performance are essential.



Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 6	GHz
VSWR	≤ 1.15	@DC-3 GHz
	≤ 1.25	@3-5 GHz
Insertion Loss	≤ 0.2	@DC-4 GHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 1.5	kVrms (at sea level)
Inner Conductor Resistance	≤ 1.5	m Ω
Outer Conductor Resistance	≤ 0.2	m Ω
Power Handling	316	W @1GHz
RF Leakage	≤ -55	dB @1GHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Brass	Gold
Outer Conductor/Body	Brass	Nickel
Back Nut	Brass	Nickel
Fastening Nut	Brass	Nickel
Dielectric	Teflon/PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Fastening Type	7/16-28	-
Contact Captivation	≥ 27	N
Coupling Nut Torque	46 - 69	Ncm
Coupling Nut Retention Force	≥ 450	N
Cable Type Compatibility	1/2" Super Flexible Cable	-
Operating Temperature	-40 ~ 85	°C
Compliance	ROHS	-