

## TNC M CRIMP for RG58/RG142/LMR195/LMR200 Cable

P/N: AT3T1D-6D

### Product Feature:

- Connector Type : TNC
- Polarity : Standard
- Gender : Male/Plug
- Geometry : Straight
- Termination Style : Crimp
- Cable : RG58/RG142/LMR195/LMR200
- Application : General Purpose/Telecom etc

The **TNC Male Crimp Connector** for **RG58, RG142, LMR195, and LMR200 Cables** is a versatile RF interface designed for permanent, high-reliability terminations on mid-diameter coaxial cables. Featuring a **threaded coupling mechanism**, it provides a more secure and **vibration-resistant connection** than bayonet-style alternatives, ensuring consistent electrical performance. The precision crimp sleeve creates a high-strength mechanical bond that maintains excellent shielding effectiveness. It is widely used in **vehicular communication systems, Wi-Fi antenna assemblies, medical instrumentation, and laboratory test leads** where a rugged, low-loss connection is essential for signal stability.



### Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	$\Omega$
Frequency Range	DC ~ 6	GHz
VSWR	$\leq 1.15$	@DC-3 GHz
	$\leq 1.25$	@3-5 GHz
Insertion Loss	$\leq 0.2$	@DC-4 GHz
Insulation Resistance	$\geq 5000$	M $\Omega$
Dielectric Withstanding Voltage	$\geq 1.5$	kVrms (at sea level)
Inner Conductor Resistance	$\leq 1.5$	m $\Omega$
Outer Conductor Resistance	$\leq 0.2$	m $\Omega$
Power Handling	316	W @1GHz
RF Leakage	$\leq -55$	dB @1GHz



## Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Brass	Gold
Outer Conductor/Body	Brass	Nickel
Ferrule	Brass	Nickel
Fastening Nut	Brass	Nickel
Dielectric	Teflon/PTFE	-
Gasket	Silicone rubber	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Fastening Type	7/16-28	-
Contact Captivation	≥ 27	N
Coupling Nut Torque	46 - 69	Ncm
Coupling Nut Retention Force	≥ 450	N
Cable Type Compatibility	RG58/RG142/LMR195/LMR200 Cable	-
Operating Temperature	-40 ~ 85	°C
Compliance	ROHS	-