

UHF M CRIMP for RG217 Cable

P/N: AT3U1D-3T

Product Feature:

- Connector Type : UHF (PL-259)
- Polarity : Standard
- Gender : Male/Plug
- Geometry : Straight
- Termination Style : Crimp
- Cable : RG217
- Application : Military Communication /Telecom etc

The **UHF Male Crimp Connector** for **RG217 cable** is a heavy-duty RF component designed for the **high-power demands** of large-diameter coaxial lines. Its robust **crimp-style termination** ensures a high-strength, gas-tight mechanical bond, providing **reliable electrical performance** up to 500 MHz. This connector is widely utilized in **high-power amateur radio, maritime communication systems, and commercial HF/VHF transmitters**. Its durable design is ideal for **industrial RF heating equipment, military communications, and base station antenna installations** requiring rugged, high-voltage signal delivery.



Electrical Specifications

Parameter	Value	Unit
Characteristic Impedance	50	Ω
Frequency Range	DC ~ 1	GHz
VSWR	≤ 1.10	@DC-500 MHz
	≤ 1.20	@500-1000 MHz
Insertion Loss	≤ 0.1	@DC-500 MHz
Insulation Resistance	≥ 5000	M Ω
Dielectric Withstanding Voltage	≥ 2.0	kVrms (at sea level)
Inner Conductor Resistance	≤ 5	m Ω
Outer Conductor Resistance	≤ 5	m Ω
Power Handling	≥ 500	W @1GHz
Shielding Effectiveness	≥ 60	dB @300 MHz



Technical Data Sheet

Material & Plating		
Component	Material	Plating
Center Conductor	Brass	Gold
Outer Conductor/Body	Brass	Tri-Alloy
Fastening Nut	Brass	Nickel
Dielectric	PTFE	-

Mechanical & Environmental Specifications		
Parameter	Value	Unit
Durability (Matings)	≥ 500 min.	-
Fastening Type	5/8-24 Threaded	-
Coupling Nut Torque	1.1	Nm
Coupling Nut Retention Force	≥ 450	N
Cable Type Compatibility	RG217 Cable	-
Operating Temperature	-40 ~ 80	°C
Compliance	ROHS	-